# Manure Master<sup>™</sup> **Mechanical Defoamer**

## A Fast-acting Mechanical Defoamer to Control Manure Foam at Pump-out

Manure Master Mechanical Defoamer is an extremely effective and fast-acting liquid manure mechanical defoamer during pump-out. Apply at pump-out to knock down mechanical foam. By using Manure Master Mechanical Defoamer, full pump-out or manure tanker capacity can be achieved.

**INGREDIENTS:** A mix of natural plant-based oils.

### **DIRECTIONS FOR USE:**

For Mechanical Foaming: Add one gallon of Manure Master Mechanical Defoamer per 100,000 to 300,000 gallons of manure and agitate. Dosage rates may vary depending on the makeup of the manure foam. Can also be mixed into manure tankers.

#### **HANDLING & STORAGE:**

FoamAway.

Store in a cool, dry space between 50-80 degrees F. Keep out of direct sunlight and do not store with strong oxidizing agents. Note: For swine methane pit foam, use biological Manure Master

WARNING: Disturbing hog pits and/or pit foam can result in the release of FLAMMABLE GASES. Before application of this product, please ensure proper ventilation to prevent the accumulation of flammable gases and extinguish all potential ignition sources, including heaters, electrical, do not smoke, etc. Failure to follow these instructions may result in a fire or explosion. Fire or explosions can lead to property damage, personal injury or loss of life.

**KEEP OUT OF REACH OF CHILDREN** 

PL-72\_052201

#### IMPORTANT NOTICE TO PURCHASER:

Seller's and manufacturer's only obligation to a purchaser or user of this product shall be to refund the purchase price or to replace the quantity purchased of any defective product. In no event shall seller or manufacturer be liable to a purchaser or user of this product for any claim for any economic, indirect, special, incidental or consequential damages, or for any injury, loss or damage, direct or indirect, to any person or property. Purchaser of this product expressly acknowledges and agrees to these



CAUTION: May cause eye and skin irritation. Avoid breathing dust/mist/ vapor/spray. Wear protective gloves/ protective clothing/eye protection/ face protection. Wash thoroughly after handling. Do not eat, drink or smoke while handling. IN EYES: Remove any contact

lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Do not use an eye ointment. Seek medical attention. IF ON SKIN: Wash skin with soap and water. IF INHALED: Move person to fresh air. IF SWALLOWED: Drink plenty of water. If irritation persists, seek medical attention.

### **GUARANTOR:**

ProfitPro. LLC 408 S. 1st Ave. Albert Lea, MN 56007 507-373-2550



MADE IN THE U.S.A.

#### **NET CONTENTS & WEIGHT:**

Buik. 8.4 pounds per gallon		
	2.5 U.S. gallons (9.46 L)	21 lbs (9.53 kg
	55 U.S. gallons (208.20 L)	462 lbs (209.56 kg
	275 U.S. gallons (1040.99 L)	2,310 lbs (1047.80 kg